

LEVELING AND STABILIZATION



	Rear Hydraulic Stabilizer Jack	Standard HLG	Pinless HLG	Heavy Duty HLG
Capacity Rating	7,000 lb. per set of 2	7,000 lb. per set of 2	7,000 lb. per set of 2	13,000 lb. per set of 2
Max Cylinder Stroke	12"	12"	26"	27"
Adjustable Footpad	Yes	Yes	Yes	No

NOTE: Do not exceed capacity rating of the hydraulic landing gear.

⚠ WARNING

Do not left unit with rear stabilizing jacks. Rear Stabilizer Jacks have the same capacity rating as the Standard HLG; however, the Rear Stabilizer Jack is designed as a “stabilizing “ jack and not a “lifting” jack. Lifting the unit with the Rear Stabilizing Jacks may result in death, serious personal injury or damage to the unit.

NOTE: Switches and/or controls may be located near HLG. HLG operator **MUST** be clear of HLG and all moving parts during operation of HLG. Contact with HLG during operation or moving parts may cause serious personal injury.

⚠ WARNING

Serious damage to the trailer frame may occur if HLG in operated unevenly. The HLG operates as a set of two legs and should operate simultaneously keeping the front of the trailer horizontal at all times. Should the HLG not operate simultaneously, stop operation immediately, retract the HLG and call: Lippert Components - service and warranty dept.

As a supplier of components to the RV industry, safety, education and customer satisfaction are our primary concerns. Should you have any questions, please do not hesitate to contact us at (574) 537-8900 or by email at customerservice@lci1.com. Self-help tips, technical documents, product videos and a training class schedule are available at www.lci1.com or by downloading the MyLCI app.